



## BSN T.S. - Pan Head Type C - H



### Cross recessed pan head tapping screws product grade A

Specification and International Standard: BS EN ISO 7049 : 1995

Material: cold heading, case hardening quality steel

Mechanical properties - international standard: ISO 2702

Surface finish: dacromet coated 500



#### Dimensions in millimetres

Thread size	ST 3.5	ST4.2	ST 4.8	ST 5.5	ST 6.3
$d_k$ (head width) max.	7	8	9.5	11	12
$d_k$ (head width) min.	6.64	7.64	9.14	10.57	11.57
$k$ (head height) max.	2.6	3.1	3.7	4.0	4.6
$k$ (head height) min.	2.35	2.8	3.4	3.7	4.3
Pitch	1.3	1.4	1.6	1.8	1.8
Recess No.	2	2	2	3	3

Details refer to standard specification

#### Description: BSN Pan Head Tapping Screw

Order designation: CK7049 + article no. (example: CK7049-35010)

$d \times L$	article no.	$d \times L$	article no.	$d \times L$	article no.
3.5 x 10	35010	4.8 x 10	48010	6.3 x 12	63012
3.5 x 12	35012	4.8 x 12	48012	6.3 x 16	63.16
3.5 x 16	35016	4.8 x 16	48016	6.3 x 19	63019
3.5 x 19	35019	4.8 x 19	48019	6.3 x 25	63.25
3.5 x 25	35025	4.8 x 25	48025	6.3 x 32	63032
3.5 x 32	35032	4.8 x 32	48032	6.3 x 37	63037
3.5 x 37	35037	4.8 x 37	48037	6.3 x 50	63050
3.5 x 50	35050	4.8 x 50	48050	6.3 x 62	63062
		4.8 x 62	48062	6.3 x 75	63075
4.2 x 10	42010	4.8 x 75	48075	6.3 x 87	63087
4.2 x 12	42012	4.8 x 100	48100	6.3 x 100	63100
4.2 x 16	42016				
4.2 x 19	42019	5.5 x 12	55012		
4.2 x 25	42025	5.5 x 16	55016		
4.2 x 32	42032	5.5 x 19	55019		
4.2 x 37	42037	5.5 x 25	55025		
4.2 x 50	42050	5.5 x 32	55032		
4.2 x 62	42062	5.5 x 37	55037		
4.2 x 75	42075	5.5 x 50	55050		
		5.5 x 62	55062		
		5.5 x 75	55075		
		5.5 x 87	55087		
		5.5 x 100	55100		

Remark: other sizes on request ([www.BSNfastener.com](http://www.BSNfastener.com))