




## Stainless steel flat washers



### Product normal & large diameter

Specifications and International Standards: FORM A BS 4320 : 1968

Specifications and International Standards: FORM C BS 4320 : 1968

Mechanical Properties - property class: A4 stainless steel

Mechanical Properties - international standards: ISO 3506

#### Dimensions in millimetres (FORM A - normal diameter)

For thread size	M5	M6	M8	M10	M12	M16	M20	M24	M27	M30
<b>d1</b> min.	5.3	6.4	8.4	10.5	13	17	21	25	28	31
<b>d1</b> max.	5.5	6.7	8.7	10.9	13.4	17.4	21.5	25.5	28.5	31.6
<b>d2</b> min.	9.7	12.1	16.6	20.5	23.5	29.5	36.2	43.2	49.2	55
<b>d2</b> max.	10	12.5	17	21	24	30	37	44	50	60
<b>s</b> min.	0.9	1.4	1.4	1.8	2.3	2.7	2.7	3.7	3.7	3.7
<b>s</b> max.	1.1	1.8	1.8	2.2	2.7	3.3	3.3	4.3	4.3	4.3

#### Dimensions in millimetres (FORM C - large diameter)

For thread size	M5	M6	M8	M10	M12	M16	M20	M24	M27	M30
<b>d1</b> min.	5.3	6.4	8.4	10.5	13	17	21	25	28	31
<b>d1</b> max.	5.5	6.7	8.7	10.9	13.4	17.4	21.5	25.5	28.5	31.6
<b>d2</b> min.	12.1	13.6	20.5	23.5	27.5	33.2	38.2	49.2	55	59
<b>d2</b> max.	12.5	14	21	24	28	34	39	50	56	60
<b>s</b> min.	0.9	1.4	1.4	1.8	2.3	2.7	2.7	3.7	3.7	3.7
<b>s</b> max.	1.1	1.8	1.8	2.2	2.7	3.3	3.3	4.3	4.3	4.3

#### example: FORM A M10

Order designation: E4320A + article no. (example: E4320A-10)

<b>example:</b>	<b>For thread size</b>	<b>article no.</b>
FORM A	M10	10

#### example: FORM C M12

Order designation: E4320C + article no. (example: E4320C-12)

<b>example:</b>	<b>For thread size</b>	<b>article no.</b>
FORM C	M12	12

([www.BSNfastener.com](http://www.BSNfastener.com))