



**LIFTING
SOCKET
with crossbar**

Ref.No. zinc plated	Re.No. Hot Dip Galv.	Ref.No. A2	Ref.No. A4	S.W. L kg	d mm	D	Dimensions mm			
							h	e	t	l
90512040G	90512040H	90512040S	90512040V	500	Rd 12 X 1.75	15	40	22	6	70
90514047G	90514047H	90514047S	90514047V	800	Rd 14 X 2.00	18	47	25	8	70
90516054G	90516054H	90516054S	90516054V	1200	Rd 16 X 2.00	21	54	27	10	100
90518065G	90518065H	90518065S	90518065V	1600	Rd 18 X 2.50	24	65	34	10	120
90520069G	90520069H	90520069S	90520069V	2000	Rd 20 X 2.50	26	69	35	12	120
90524078G	90524078H	90524078S	90524076V	2500	Rd 24 X 3.00	30.3	78	43	12	150
90530103G	90530103H	90530103S	90530103V	4000	RD 30 X 3.50	39.5	103	56	18	200
90536125G	90536125H	90536125S	90536125V	6300	Rd 36 X 4.00	47	125	68	22	250
90542145G	90542145H	90542145S	90542145V	8000	Rd 42 X 4.50	54	145	80	26	300
90552195G	90552195H	90552195S	90552195V	12500	Rd 52 X 5.00	67.2	195	97	36	350